

VIM

hspark@hancom.com

Favorite Ranking #1

- *SEATTLE, WA - - Linux Journal, a publication of Specialized Systems Consultants, Inc. (SSC), has announced the winners of the 2003 Readers' Choice Awards. Over 7,500 readers visited the Linux Journal web site and voted on their top choices in 28 categories. For more information on the winners please see the feature article in the November issue of Linux Journal (#115).*
- Favorite Audio Tool: XMMS
Favorite Backup Utility: TAR
Most Indispensable Linux Book: LINUX IN A NUTSHELL 3RD ED., by ELLEN SIEVER, ET AL.
Favorite Web Browser: MOZILLA
Favorite Linux Journal Column: COOKING WITH LINUX
Favorite Database: MYSQL
Favorite Desktop Workstation: HOMEMADE
Favorite Distributed File-Sharing System: GNUTELLA
Favorite Distribution: DEBIAN
Favorite Programming Beverage: COFFEE

Favorite Ranking #1

- Favorite E-mail Client: EVOLUTION
- Favorite Embedded Distribution: QTOPIA
- Favorite Linux Game: FROZEN BUBBLE
- Favorite Graphics Program: THE GIMP
- Favorite Instant-Messaging Client: GAIM
- Favorite Programming Language: C++
- Favorite Office Program: OPENOFFICE.ORG
- Favorite Processor Architecture: AMD ATHLON
- Favorite Portable Workstation: QLI 15" AMD NOTEBOOKS
- Favorite Network or Server Appliance: CYCLADES ALTERPATH ACS
- Favorite Server: SGI ALTIX 3000
- Favorite System Administration Tool: WEBMIN
- Favorite Text Editor: VIM
- Favorite Development Tool: GCC
- Favorite Linux Training: SUSE LINUX TRAINING
- Favorite Linux Web Site: SLASHDOT
- Favorite Web-Hosting Service: RACKSPACE
- Favorite Desktop Environment: KDE

가

- ()

-

가 -> Entertainment

- ()

-

->

- ()

- Communication data

Vim

- - H/W , S/W , ,
- - - > > > > **Coding** > Compile >.. ..
 - > >
 - - **Functional** > **Event** > **Component**
 - >
- - -> Playing
UI

Vim :

- :help command
- 05.1 vimrc
- 08.* Splitting windows
- 24.7 Abbreviations
- 40.1 Key mapping
- User command
- Pattern
- Tags

Vim :

- Pattern
- :help pattern
- pattern ::= branch
 - or branch \ | branch
 - or branch \ | branch \ | branch
 - etc.
- branch ::= concat
 - or concat \ & concat
 - or concat \ & concat \ & concat
 - etc.
- concat ::= piece
 - or piece piece
 - or piece piece piece
 - etc.
- piece ::= atom
 - or atom multi

Vim :

multi ~

'magic' 'nomagic'

matches of the preceding atom ~

/star	*	*	0 or more	as many as possible
/\+	\+	\+	1 or more	as many as possible (*)
/\=	\=	\=	0 or 1	as many as possible (*)
/\?	\?	\?	0 or 1	as many as possible (*)
/\{		\{n,m}	\{n,m} n to m	as many as possible (*)
	\{n}	\{n}	n	exactly (*)
	\{n,}	\{n,}	at least n	as many as possible (*)
	\{,m}	\{,m}	0 to m	as many as possible (*)
	\{ }	\{ }	0 or more	as many as possible (same as *) (*)
/\{-	\{-n,m}	\{-n,m}	n to m	as few as possible (*)
	\{-n}	\{-n}	n	exactly (*)
	\{-n,}	\{-n,}	at least n	as few as possible (*)
	\{-,m}	\{-,m}	0 to m	as few as possible (*)
	\{-}	\{-}	0 or more	as few as possible (*)

Vim :



Vim : Tip

Mode	Key press		
Normal	*	:	
Normal	de	:	
Normal	df<char>	:	<char>
Normal	.	:	
Normal	=	:	indent
Normal	zf	:	
Visual	O	:	Visual select cursor
Command	:set paste	:	Text

Vim :

가

- - 3 editing pattern
- 가
 -
 -
 - Vim Game

Vim :

c/c++

- Open Source Out Sourcing
- ctags
 - `ctags -R */*`
 - Tlist.vim : <http://www.vim.org>

Sample 1

```
CREATE TABLE users (  
  no int(11) NOT NULL,  
  id varchar(16) NOT NULL default '',  
  gid int(11) NOT NULL default '0',  
  password varchar(32) NOT NULL default '',  
  name varchar(30) NOT NULL default '',  
  status int(11) NOT NULL default '0',  
  email varchar(50) NOT NULL default '',  
  :  
  :  
  cono varchar(12) default NULL,  
  productmail char(1) NOT NULL default '1',  
  motive varchar(100) default NULL,  
  PRIMARY KEY (uno),  
  UNIQUE KEY uid (uid));
```

```
$resultRow[$i][NO]           = $row[NO];  
$resultRow[$i][ID]          = $row[ID];  
$resultRow[$i][GID]         = $row[GID];  
$resultRow[$i][PASSWORD]    = $row[PASSWORD];  
$resultRow[$i][NAME]        = $row[NAME];  
$resultRow[$i][STATUS]      = $row[STATUS];  
$resultRow[$i][EMAIL]       = $row[EMAIL];  
:  
:  
$resultRow[$i][CONO]         = $row[CONO];  
$resultRow[$i][PRODUCTMAIL] = $row[PRODUCTMAIL];  
$resultRow[$i][MOTIVE]      = $row[MOTIVE];
```

```
:s/^\ (\s* \) \ (\w* \) \ > \ (. * \) / \ 2/g<CR>
```

```
:'<,'>s/^\.*$/$resultRow[$i][ \ U& \ E]^!^! = $row[ \ U& \ E];/g
```

Sample 2

- vCard MIME Directory Profile RFC-2426
 - <http://www.faqs.org/rfcs/rfc2426.html>
 - `:%g!/^ \ s*Type \ s*name: \ s[A-Z]*/d`
 - `:'<,'>s/^.*://g`
 - `:s/^ \ (\ s* \) \ (\ w* \) \ > \ (. * \) / \ 2/g<CR>`
 - `:'<,'>s/^.*$/if(ereg($regGROUP."&$", $arKey[0])) { \ r \ r}/g`